

Package: PeakError (via r-universe)

August 28, 2024

Maintainer Toby Dylan Hocking <toby.hocking@r-project.org>

Author Toby Dylan Hocking

Version 2023.9.4

License GPL-3

Title Compute the Label Error of Peak Calls

Description Chromatin immunoprecipitation DNA sequencing results in genomic tracks that show enriched regions or peaks where proteins are bound. This package implements fast C code that computes the true and false positives with respect to a database of annotated region labels.

Suggests testthat, ggplot2

Repository <https://tdhock.r-universe.dev>

RemoteUrl <https://github.com/tdhock/peakerror>

RemoteRef HEAD

RemoteSha 96c7a051aa244895e74c44802020beabdca7f33

Contents

checkChrom	2
checkPositions	2
PeakError	3
PeakErrorChrom	4
Peaks	5

Index	6
--------------	----------

checkChrom

checkChrom

Description

Check for a valid data.frame with chrom names.

Usage

```
checkChrom(df)
```

Arguments

df

df

Author(s)

Toby Dylan Hocking

checkPositions

checkPositions

Description

Check for a valid data.frame with chromStart, chromEnd.

Usage

```
checkPositions(df)
```

Arguments

df

df

Author(s)

Toby Dylan Hocking

PeakError	<i>PeakError</i>
-----------	------------------

Description

Compute true and false positive peak calls, with respect to a database of annotated regions.

Usage

```
PeakError(peaks, regions)
```

Arguments

peaks	data.frame with columns chrom, chromStart, chromEnd. NOTE: chromStart should be 0-based and chromEnd should be 1-based. EXAMPLE: the first 100 base of of a chromosome are chromStart=0, chromEnd=100. The second 100 bases are chromStart=100, chromEnd=200.
regions	data.frame with columns chrom, chromStart, chromEnd, annotation.

Value

data.frame for each region with additional counts of true positives (tp, possible.tp), false positives (fp, possible.fp, fp.status), and false negatives (fn, fn.status).

Author(s)

Toby Dylan Hocking

Examples

```
x <- seq(5, 85, by=5)
peaks <- rbind(
  Peaks("chr2", x, x+3),
  Peaks("chr3", c(25, 38, 57), c(33, 54, 75)),
  Peaks("chr4", c(5, 32, 38, 65), c(15, 35, 55, 85)),
  Peaks("chr5", c(12, 26, 56, 75), c(16, 54, 59, 85)))
regions.list <- list()
for(chr in 1:5){
  regions.list[[chr]] <- data.frame(
    chrom=paste0("chr", chr),
    chromStart=c(10, 30, 50, 70),
    chromEnd=c(20, 40, 60, 80),
    annotation=c("noPeaks", "peakStart", "peakEnd", "peaks"))
}
regions <- do.call(rbind, regions.list)
err <- PeakError(peaks, regions)
ann.colors <- c(
  noPeaks="#f6f4bf",
  peakStart="#ffafaf",
```

```

peakEnd="#ff4c4c",
peaks="#a445ee")
if(require(ggplot2)){
  ggplot()+
  geom_rect(aes(
    xmin=chromStart+1/2, xmax=chromEnd+1/2,
    ymin=-1, ymax=1,
    fill=annotation,
    linetype=fn.status,
    size=fp.status),
    data=err, color="black")+
  scale_y_continuous("", breaks=NULL)+
  scale_linetype_manual(
    values=c("false negative"="dotted", correct="solid"))+
  scale_size_manual(
    values=c("false positive"=3, correct=1))+
  scale_fill_manual(
    values=ann.colors,
    breaks=names(ann.colors))+
  facet_grid(chrom ~ .)+
  theme_bw()+
  guides(
    fill=guide_legend(order=1),
    linetype=guide_legend(order=2, override.aes=list(fill="white")),
    size=guide_legend(order=3, override.aes=list(fill="white")))+
  theme(panel.margin=grid::unit(0, "cm"))+
  geom_segment(aes(
    chromStart+1/2, 1/2, xend=chromEnd+1/2, yend=1/2),
    data=peaks, color="deepskyblue", size=2)+
  scale_x_continuous(
    "position on chromosome",
    breaks=seq(10, 90, by=10))+
  geom_text(aes(
    base, -1/2, label="N"),
    data.frame(base=10:90),
    color="deepskyblue")
}

```

PeakErrorChrom

PeakErrorChrom

Description

Compute the [PeakError](#) assuming that peaks and regions are on the same chrom.

Usage

```
PeakErrorChrom(peaks,
  regions)
```

Arguments

peaks data.frame with columns chromStart, chromEnd. NOTE: chromStart should be 0-based and chromEnd should be 1-based. EXAMPLE: the first 100 base of of a chromosome are chromStart=0, chromEnd=100. The second 100 bases are chromStart=100, chromEnd=200.

regions data.frame with columns chromStart, chromEnd.

Value

data.frame with 1 row for each region and error columns.

Author(s)

Toby Dylan Hocking

Peaks

Peaks

Description

Make a data.frame that represents a list of peaks.

Usage

```
Peaks(chrom = factor(),  
      base.before = integer(),  
      last.base = integer())
```

Arguments

chrom character or factor with chrom name for example "chr22"

base.before integer, base before peak.

last.base integer, last base of peak.

Value

data.frame with columns chrom, chromStart, chromEnd.

Author(s)

Toby Dylan Hocking

Index

checkChrom, [2](#)
checkPositions, [2](#)

PeakError, [3](#), [4](#)
PeakErrorChrom, [4](#)
Peaks, [5](#)